



Spare part SIMATIC S7-300, CPU 317-2DP, Central processing unit with 512 KB work memory, 1st interface MPI/DP 12 Mbit/s, 2nd interface DP master/slave Micro Memory Card required

| General information | |
|---|---|
| HW functional status | 01 |
| Firmware version | V2.6 |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V5.2 + SP1 or higher with HW update |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| external protection for power supply lines (recommendation) | 2 A min. |
| Input current | |
| Current consumption (rated value) | 850 mA |
| Current consumption (in no-load operation), typ. | 100 mA |
| Inrush current, typ. | 2.5 A |
| I ² t | 1 A ² ·s |
| Power loss | |
| Power loss, typ. | 4 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated | 512 kbyte |
| <ul style="list-style-type: none"> expandable | No |
| Load memory | |
| <ul style="list-style-type: none"> Plug-in (MMC) | Yes |
| <ul style="list-style-type: none"> Plug-in (MMC), max. | 8 Mbyte |
| <ul style="list-style-type: none"> Data management on MMC (after last programming), min. | 10 y |
| Backup | |
| <ul style="list-style-type: none"> present | Yes; Guaranteed by MMC (maintenance-free) |
| <ul style="list-style-type: none"> without battery | Yes; Program and data |
| CPU processing times | |
| for bit operations, typ. | 0.05 μs |
| for word operations, typ. | 0.2 μs |
| for fixed point arithmetic, typ. | 0.2 μs |
| for floating point arithmetic, typ. | 1 μs |
| CPU-blocks | |
| Number of blocks (total) | 2 048; (DBs, FCs, FBs OBs, SDBs); the maximum number of loadable blocks can be reduced by the MMC being used. |
| DB | |


| | |
|--|--|
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 047; Number band: 1 to 2047 64 kbyte |
| FB | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 048; Number range: 0 to 2047 64 kbyte |
| FC | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 048; Number range: 0 to 2047 64 kbyte |
| OB | |
| <ul style="list-style-type: none"> • Size, max. • Number of free cycle OBs • Number of time alarm OBs • Number of delay alarm OBs • Number of cyclic interrupt OBs • Number of process alarm OBs • Number of DPV1 alarm OBs • Number of isochronous mode OBs • Number of startup OBs • Number of asynchronous error OBs • Number of synchronous error OBs | 64 kbyte 1; OB 1 1; OB 10 2; OB 20, 21 4; OB 32, 33, 34, 35 1; OB 40 3; OB 55, 56, 57 1; OB 61 1; OB 100 5; OB 80, 82, 85, 86, 87 2; OB 121, 122 |
| Nesting depth | |
| <ul style="list-style-type: none"> • per priority class • additional within an error OB | 16 4 |
| Counters, timers and their retentivity | |
| S7 counter | |
| <ul style="list-style-type: none"> • Number | 512 |
| Retentivity | |
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 511 |
| — preset | Z 0 to Z 7 |
| Counting range | |
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 999 |
| IEC counter | |
| <ul style="list-style-type: none"> • present • Type • Number | Yes SFB Unlimited (limited only by RAM capacity) |
| S7 times | |
| <ul style="list-style-type: none"> • Number | 512 |
| Retentivity | |
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 511 |
| — preset | No retentivity |
| Time range | |
| — lower limit | 10 ms |
| — upper limit | 9 990 s |
| IEC timer | |
| <ul style="list-style-type: none"> • present • Type • Number | Yes SFB Unlimited (limited only by RAM capacity) |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 256 kbyte |
| Flag | |
| <ul style="list-style-type: none"> • Size, max. • Retentivity available • Retentivity preset • Number of clock memories | 4 096 byte Yes; From MB 0 to MB 4 095 MB 0 to MB 15 8; 1 memory byte |

| | |
|---|---|
| Data blocks | |
| • Retentivity adjustable | Yes; via non-retain property on DB |
| • Retentivity preset | Yes |
| Local data | |
| • per priority class, max. | 1 024 byte |
| Address area | |
| I/O address area | |
| • Inputs | 8 192 byte |
| • Outputs | 8 192 byte |
| of which distributed | |
| — Inputs | 8 192 byte |
| — Outputs | 8 192 byte |
| Process image | |
| • Inputs | 2 048 byte |
| • Outputs | 2 048 byte |
| • Inputs, adjustable | 2 048 byte |
| • Outputs, adjustable | 2 048 byte |
| • Inputs, default | 256 byte |
| • Outputs, default | 256 byte |
| Subprocess images | |
| • Number of subprocess images, max. | 1 |
| Digital channels | |
| • Inputs | 65 536 |
| — of which central | 1 024 |
| • Outputs | 65 536 |
| — of which central | 1 024 |
| Analog channels | |
| • Inputs | 4 096 |
| — of which central | 256 |
| • Outputs | 4 096 |
| — of which central | 256 |
| Hardware configuration | |
| Number of expansion units, max. | 3 |
| Number of DP masters | |
| • integrated | 2 |
| • via CP | 4 |
| Number of operable FMs and CPs (recommended) | |
| • FM | 8 |
| • CP, PtP | 8 |
| • CP, LAN | 10 |
| Rack | |
| • Racks, max. | 4 |
| • Modules per rack, max. | 8 |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • retentive and synchronizable | Yes |
| • Backup time | 6 wk; At 40 °C ambient temperature |
| • Deviation per day, max. | 10 s |
| • Behavior of the clock following POWER-ON | Clock continues running after POWER OFF |
| • Behavior of the clock following expiry of backup period | the clock continues at the time of day it had when power was switched off |
| Operating hours counter | |
| • Number | 4 |
| • Number/Number range | 0 to 3 |
| • Range of values | 0 to 2 ³¹ hours (when using SFC 101) |
| • Granularity | 1 h |
| • retentive | Yes; Must be restarted at each restart |
| Clock synchronization | |
| • supported | Yes |

| | |
|--|---|
| • to MPI, master | Yes |
| • to MPI, slave | Yes |
| • to DP, master | Yes; With DP slave only slave clock |
| • to DP, slave | Yes |
| • in AS, master | Yes |
| • in AS, slave | Yes |
| • on Ethernet via NTP | No |
| Digital inputs | |
| integrated channels (DI) | 0 |
| Digital outputs | |
| integrated channels (DO) | 0 |
| Analog inputs | |
| integrated channels (AI) | 0 |
| Analog outputs | |
| integrated channels (AO) | 0 |
| Interfaces | |
| Number of industrial Ethernet interfaces | 0 |
| Number of PROFINET interfaces | 0 |
| Number of RS 485 interfaces | 2; Combined MPI / PROFIBUS DP and PROFIBUS DP |
| Number of RS 422 interfaces | 0 |
| 1. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | Yes |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP slave | Yes |
| • Point-to-point connection | No |
| MPI | |
| • Number of connections | 32 |
| • Transmission rate, max. | 12 Mbit/s |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | Yes |
| — S7 basic communication | Yes |
| — S7 communication | Yes |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| PROFIBUS DP master | |
| • Transmission rate, max. | 12 Mbit/s |
| • Number of DP slaves, max. | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | No |
| — SYNC/FREEZE | Yes |
| — Activation/deactivation of DP slaves | Yes |
| — Number of DP slaves that can be simultaneously activated/deactivated, max. | 4 |

| | |
|---|----------------------------------|
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 096 byte |
| — Outputs, max. | 8 096 byte |
| User data per DP slave | |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| PROFIBUS DP slave | |
| • Transmission rate, max. | 12 Mbit/s |
| • automatic baud rate search | Yes; only with passive interface |
| • Address area, max. | 32 |
| • User data per address area, max. | 32 byte |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes; Only with active interface |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Direct data exchange (slave-to-slave communication) | Yes |
| — DPV1 | No |
| Transfer memory | |
| — Inputs | 244 byte |
| — Outputs | 244 byte |
| 2. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | No |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP slave | Yes |
| • Point-to-point connection | No |
| PROFIBUS DP master | |
| • Number of connections, max. | 32 |
| • Transmission rate, max. | 12 Mbit/s |
| • Number of DP slaves, max. | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | Yes; OB 61 |
| — SYNC/FREEZE | Yes |
| — Activation/deactivation of DP slaves | Yes |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 096 byte |
| — Outputs, max. | 8 096 byte |
| User data per DP slave | |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |

| PROFIBUS DP slave | |
|---|--|
| • Number of connections | 32 |
| • GSD file | The latest GSD file is available at: http://www.siemens.com/profibus-gsd |
| • Transmission rate, max. | 12 Mbit/s |
| • automatic baud rate search | Yes; only with passive interface |
| • Address area, max. | 32 |
| • User data per address area, max. | 32 byte |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes; with interface active |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Direct data exchange (slave-to-slave communication) | Yes |
| — DPV1 | No |
| Transfer memory | |
| — Inputs | 244 byte |
| — Outputs | 244 byte |
| Protocols | |
| PROFIsafe | No |
| communication functions / header | |
| PG/OP communication | Yes |
| Data record routing | No |
| Global data communication | |
| • supported | Yes |
| • Number of GD loops, max. | 8 |
| • Number of GD packets, max. | 8 |
| • Number of GD packets, transmitter, max. | 8 |
| • Number of GD packets, receiver, max. | 8 |
| • Size of GD packets, max. | 22 byte |
| • Size of GD packet (of which consistent), max. | 22 byte |
| S7 basic communication | |
| • supported | Yes |
| • User data per job, max. | 76 byte |
| • User data per job (of which consistent), max. | 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server) |
| S7 communication | |
| • supported | Yes |
| • as server | Yes |
| • as client | Yes; Via CP and loadable FB |
| • User data per job, max. | 180 byte; With PUT/GET |
| • User data per job (of which consistent), max. | 160 byte; as server |
| S5 compatible communication | |
| • supported | Yes; via CP and loadable FC |
| Number of connections | |
| • overall | 32 |
| • usable for PG communication | 31 |
| — reserved for PG communication | 1 |
| — adjustable for PG communication, min. | 1 |
| — adjustable for PG communication, max. | 31 |
| • usable for OP communication | 31 |
| — reserved for OP communication | 1 |
| — adjustable for OP communication, min. | 1 |
| — adjustable for OP communication, max. | 31 |
| • usable for S7 basic communication | 30 |
| — reserved for S7 basic communication | 0 |
| — adjustable for S7 basic communication, min. | 0 |

| | |
|--|---|
| — adjustable for S7 basic communication, max. | 30 |
| • usable for routing | 8 |
| S7 message functions | |
| Number of login stations for message functions, max. | 32; Depending on the configured connections for PG/OP and S7 basic communication |
| Process diagnostic messages | Yes |
| simultaneously active Alarm-S blocks, max. | 60 |
| Test commissioning functions | |
| Status block | Yes |
| Single step | Yes |
| Number of breakpoints | 2 |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs, outputs, memory bits, DB, times, counters |
| • Number of variables, max. | 30 |
| — of which status variables, max. | 30 |
| — of which control variables, max. | 14 |
| Forcing | |
| • Forcing | Yes |
| • Forcing, variables | Inputs, outputs |
| • Number of variables, max. | 10 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 100 |
| — adjustable | No |
| — of which powerfail-proof | 100 |
| configuration / header | |
| Configuration software | |
| • STEP 7 | Yes; V5.2 SP1 or higher with HW update |
| configuration / programming / header | |
| • Command set | see instruction list |
| • Nesting levels | 8 |
| • System functions (SFC) | see instruction list |
| • System function blocks (SFB) | see instruction list |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — CFC | Yes |
| — GRAPH | Yes |
| — HiGraph® | Yes |
| Know-how protection | |
| • User program protection/password protection | Yes |
| Dimensions | |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 130 mm |
| Weights | |
| Weight, approx. | 460 g |
| last modified: | 8/24/2021  |