

**SIEMENS**

12.04.2022 11:05:45 AM

6GK5206-2GS00-2FC2

SCALANCE XC206-2SFP G EEC manageable Layer 2 IE switch; IEC 62443-4-2 certified; 6x 10/100/1000 Mbit/s RJ45 ports; 2x 1000 Mbit/s SFP; 1x console port; diagnostics LED; redundant power supply; with painted printed-circuit boards; NAMUR NE21-compliant; temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail/wall; redundancy functions; office features (RSTP, VLAN,...); PROFINET IO device; Ethernet/IP-compliant; C-PLUG slot;

List Price [Show prices](#)**Customer Price** [Show prices](#)DataSheet in PDF [Download](#)Service & Support (Manuals, Certificates, FAQs...) [Download](#)**Accessory**
(74)

6GK1900-0AQ00

C-PLUG removable data storage medium for easy replacement of the devices in case of fault or failure f...



6GK1901-1BB10-2AA0

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s...



6GK1901-1BB10-2AB0

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s...



6GK1901-1BB10-2AE0

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s...

[Show all](#)**Product**

Article Number (Market Facing Number)

6GK5206-2GS00-2FC2

Product Description

SCALANCE XC206-2SFP G EEC manageable Layer 2 IE switch; IEC 62443-4-2 certified; 6x 10/100/1000 Mbit/s RJ45 ports; 2x 1000 Mbit/s SFP; 1x console port; diagnostics LED; redundant power supply; with painted printed-circuit boards; NAMUR NE21-compliant; temperature range -40 °C to +70 °C; assembly: DIN rail/S7 mounting rail/wall; redundancy functions; office features (RSTP, VLAN,...); PROFINET IO device; Ethernet/IP-compliant; C-PLUG slot;

Product family

SCALANCE XC-200EEC managed

Product Lifecycle (PLM)

PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group

5C2 / 5C2

List Price

[Show prices](#)

Customer Price

[Show prices](#)

Surcharge for Raw Materials

None

Metal Factor

None

Delivery information

Export Control Regulations

AL : N / ECCN : N

Standard lead time ex-works

180 Day/Days

Net Weight (kg)

0,520 Kg

Packaging Dimension

19,30 x 25,20 x 14,20

Package size unit of measure

CM

Quantity Unit

1 Piece

Packaging Quantity

1

Additional Product Information

EAN

4047622614327

UPC

804766812316

Commodity Code

85176200

LKZ_FDB/ CatalogID

IK

Product Group

4D83

Group Code

R320

Country of origin

Germany

Compliance with the substance restrictions according to RoHS directive

Given

Product class

A: Standard product which is a stock item could be returned within the returns guidelines/period.

WEEE (2012/19/EU) Take-Back Obligation

Yes

REACH Art. 33 Duty to inform according to the current list of candidates

Classifications

	Version	Classification
eClass	6	19-17-01-06
eClass	7.1	19-17-01-06
eClass	8	19-17-01-06
eClass	9	19-17-01-06
eClass	9.1	19-17-01-06
ETIM	5	EC000734
ETIM	6	EC000734
ETIM	7	EC000734
ETIM	8	EC000734
IDEA	4	6817
UNSPSC	15	43-22-26-12
