

# Product datasheet

Specifications



## iC60N - miniature circuit breaker - 4P - 6A - C curve

A9F74406

### Main

|                           |   |
|---------------------------|---|
| Device application        | Distribution  |
| Range                     | Acti9   |
| product name              | Acti9 iC60  |
| Product or component type | Miniature circuit-breaker   |
| Device short name         | IC60N   |
| Poles description         | 4P  |
| Number of protected poles | 4   |
| [In] rated current        | 6 A   |
| network type              | DC<br>AC  |
| Trip unit technology      | Thermal-magnetic  |
| Curve code                | C   |
| Breaking capacity         | 6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>36 kA Icu at 12...133 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 kA Icu at <= 250 V DC conforming to EN/IEC 60947-2<br>10 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>20 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>6 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Utilisation category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2   |
| Suitability for isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2  |
| Standards                 | EN 60898-1<br>IEC 60947-2<br>IEC 60898-1<br>EN 60947-2  |

### Complementary

|                         |                 |
|-------------------------|-----------------|
| Network frequency       | 50/60 Hz        |
| Magnetic tripping limit | 8 x In +/- 20 % |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|   |  |
|---|--|
| <b>[Ics] rated service breaking capacity</b>            | 15 kA 75 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 75 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 kA 75 % conforming to EN 60947-2 - 440 V AC 50/60 Hz<br>15 kA 75 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 75 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 kA 75 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>27 kA 75 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz<br>27 kA 75 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz<br>6000 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz<br>6000 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz<br>10 kA 100 % conforming to IEC 60947-2 - 180...250 V DC<br>10 kA 100 % conforming to EN 60947-2 - 180...250 V DC |
| <b>Limitation class</b>                                 | 3 conforming to EN 60898-1<br>3 conforming to IEC 60898-1  |
| <b>[Ui] rated insulation voltage</b>                    | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2  |
| <b>[Uimp] rated impulse withstand voltage</b>           | 6 kV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2  |
| <b>Contact position indicator</b>                       | Yes  |
| <b>Control type</b>                                     | Toggle   |
| <b>Local signalling</b>                                 | Trip indicator   |
| <b>Mounting mode</b>                                    | Fixed  |
| <b>Mounting support</b>                                 | DIN rail   |
| <b>Comb busbar and distribution block compatibility</b> | Top or bottom: YES   |
| <b>9 mm pitches</b>                                     | 8  |
| <b>Height</b>   | 85 mm  |
| <b>Width</b>  | 72 mm  |
| <b>Depth</b>  | 78.5 mm  |
| <b>Product weight</b>                                   | 0.5 kg   |
| <b>Colour</b>   | White  |
| <b>Mechanical durability</b>                            | 20000 cycles   |
| <b>Electrical durability</b>                            | 10000 cycles   |
| <b>Connections - terminals</b>                          | Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid<br>Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible  |
| <b>Wire stripping length</b>                            | 14 mm for top or bottom connection   |
| <b>Tightening torque</b>                                | 2 N.m top or bottom  |
| <b>Earth-leakage protection</b>                         | Separate block   |

## Environment

|  |   |
|--|---|
| <b>IP degree of protection</b>               | IP20 conforming to IEC 60529<br>IP20 conforming to EN 60529 |
| <b>Pollution degree</b>                      | 3 conforming to EN 60947-2<br>3 conforming to IEC 60947-2   |
| <b>overvoltage category</b>                  | IV  |
| <b>Tropicalisation</b>                       | 2 conforming to IEC 60068-1                                 |
| <b>Relative humidity</b>                     | 95 % at 55 °C   |
| <b>Operating altitude</b>                    | 0...2000 m  |
| <b>Ambient air temperature for operation</b> | -35...70 °C   |
| <b>Ambient air temperature for storage</b>   | -40...85 °C   |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 7.500 cm  |
| Package 1 Width              | 7.200 cm  |
| Package 1 Length             | 9.500 cm  |
| Package 1 Weight             | 429.000 g |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 3         |
| Package 2 Height             | 8.000 cm  |
| Package 2 Width              | 9.800 cm  |
| Package 2 Length             | 22.500 cm |
| Package 2 Weight             | 1.356 kg  |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 33        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 15.427 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **25**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Packaging

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**


SCIP Number **26ff71d1-98cf-4280-8725-455b9a6b2fb9**

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Take-back **No**