

# Product datasheet

Specifications



## Circuit breaker frame, MasterPact NW16N1, 1600A, 42kA/440VAC 50/60Hz (Icu), 3 poles, fixed, without control unit

48042

### Main

Range	MasterPacT
product name	MasterPact NW
Circuit breaker name	MasterPact NW16N1
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	3P
Control unit	Without control unit
[In] rated current	1600 A at 40 °C
Performance type	N1 42 kA 440 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Fixed

### Complementary

[Icu] rated ultimate short-circuit breaking capacity	42 kA at 220/415 V AC 50/60 Hz 42 kA at 440 V AC 50/60 Hz 42 kA at 525 V AC 50/60 Hz 42 kA at 690 V AC 50/60 Hz
[Ics] rated service breaking capacity	42 kA at 220/415 V AC 50/60 Hz 42 kA at 440 V AC 50/60 Hz 42 kA at 525 V AC 50/60 Hz 42 kA at 690 V AC 50/60 Hz
[Icw] rated short-time withstand current	42 kA 1 s 22 kA 3 s
[Icm] rated short-circuit making capacity	88 kA 220/415 V AC at 50/60 Hz 88 kA 440 V AC at 50/60 Hz 88 kA 525 V AC at 50/60 Hz 88 kA 690 V AC at 50/60 Hz
Sensor rating	800 A 1600 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	220 W
Maximum breaking time	25 ms

<b>Maximum closing response time</b>	70 ms
<b>Mounting support</b>	Backplate Rails
<b>Upside connection</b>	Front Rear
<b>Downside connection</b>	Front Rear
<b>Connection pitch</b>	115 mm
<b>Mechanical durability</b>	12500 cycles without maintenance 25000 cycles with maintenance
<b>Electrical durability</b>	10000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2
<b>Height</b>	352 mm
<b>Width</b>	422 mm
<b>Depth</b>	297 mm
<b>Product weight</b>	50 kg
<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-2
<b>Product certifications</b>	CE CCC EAC

## Environment

<b>IP degree of protection</b>	IP30 conforming to IEC 60529
<b>Pollution degree</b>	4 conforming to IEC 60664-1
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Operating altitude</b>	0...2000 m without derating 2000 m...5000 m with derating

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	34.0 cm
<b>Package 1 Width</b>	40.0 cm
<b>Package 1 Length</b>	31.0 cm
<b>Package 1 Weight</b>	41.251 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **1588**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**

SCIP Number **6a3c1e0b-44cb-4a11-80eb-a083722777c1**

China RoHS Regulation [China RoHS declaration](#)

PVC free **Yes**

Silicon free **No**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Halogen content performance **Product contains halogen above thresholds**

Take-back **No**