

Product datasheet

Specifications



C60 - circuit breaker - C60N - 3P - 40A - C curve

24354

⚠ Discontinued on: 23 Jan 2021

EAN Code: 3303430243540

⚠ Discontinued

Main

Range of product	C60
Range	Multi9
product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	40 A at 30 °C
network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	6000 A Icn at 400 V AC conforming to IEC 60898 10 kA Icu at 400...415 V AC conforming to EN/IEC 60947-2 20 kA Icu at 230...240 V AC conforming to EN/IEC 60947-2 6 kA Icu at 440 V AC conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

[Ue] rated operational voltage	440 V AC 400 V AC 400...415 V AC 230...240 V AC
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	15 kA conforming to EN/IEC 60947-2 - 230...240 V AC 4.5 kA conforming to EN/IEC 60947-2 - 440 V AC 7.5 kA conforming to EN/IEC 60947-2 - 400...415 V AC 6000 A conforming to IEC 60898 - 400 V AC
[Ui] rated insulation voltage	500 V AC conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6

Height	81 mm
Width	54 mm
Depth	73 mm
Product weight	0.36 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals25 mm ² flexible Tunnel type terminals35 mm ² rigid
Tightening torque	3.5 N.m
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60947-2 IEC 60898
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	5.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	0.352 kg

Contractual warranty

Warranty	18 months
-----------------	-----------