

Product datasheet

Specifications



C60 - circuit breaker - C60N - 1P - 6A - C curve

24399

⚠ Discontinued on: Jun 30, 2021 AD

⚠ Discontinued

Main

Range of product	C60
Range	Multi9
product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	1P
Number of protected poles	1
[In] rated current	6 A at 30 °C
network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	6000 A Icn at 230...400 V AC conforming to IEC 60898 10 kA Icu at 230...240 V AC conforming to EN/IEC 60947-2 15 kA Icu at 60 V DC conforming to EN/IEC 60947-2 20 kA Icu at 130 V AC conforming to EN/IEC 60947-2 3 kA Icu at 400...415 V AC conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

[Ue] rated operational voltage	400...415 V AC 230...240 V AC 230...400 V AC 130 V AC
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	15 kA conforming to EN/IEC 60947-2 - 130 V AC 2.25 kA conforming to EN/IEC 60947-2 - 400...415 V AC 7.5 kA conforming to EN/IEC 60947-2 - 230...240 V AC 6000 A conforming to IEC 60898 - 230...400 V AC
[Ui] rated insulation voltage	500 V AC conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail

9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	73 mm
Product weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals16 mm ² flexible Tunnel type terminals25 mm ² rigid

Environment

Standards	IEC 60898 EN/IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	1.7 cm
Package 1 Length	8.4 cm
Package 1 Weight	105 g

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Repack and remanufacture

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins