

voltage release MX - 200..250 V DC/AC 50/60 Hz

47363

Main

Range	MasterPacT	
Range of product	MasterPact NT MasterPact NW MasterPact NW DC	
Device short name	MX	
Product or component type	Voltage release	
Device application	Control	
Voltage release type	Opening coil Instantaneous voltage release	
control type	Standard	
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC	
Circuit breaker mounting mode	Fixed	
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW Masterpact MasterPact NW DC	

Complementary

Operating threshold	0.71.1 x Un opening	
Response time	50 ms +/- 10 % for MasterPact NT 50 ms +/- 10 % for MasterPact NW	
Supply holding power	4 5 VA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	6.000 cm
Package 1 Length	8.500 cm
Package 1 Weight	173.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm

Package 2 Weight	3.720 kg
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	71.520 kg

Contractual warranty

Warranty 12 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	23
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	Ad764790-535b-4a4e-825e-50fd804b5824
China RoHS Regulation	China RoHS declaration
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Product contains halogen above thresholds
Take-back	No