

# TeSys Deca, thermal overload relay, 0.4 to 0.63 A, class 10A

LRD04

Product availability: Stock - Normally stocked in distribution facility

### Main

Range	TeSys TeSys Deca	
product name	TeSys LRD TeSys Deca	
Product or Component Type	Differential thermal overload relay	
Device short name	LRD	
Relay application	Motor protection	
Product Compatibility	LC1D25 LC1D38 LC1D32 LC1D18 LC1D12 LC1D09	
network type	AC DC	
Thermal overload class	Class 10A IEC 60947-4-1	
Thermal protection adjustment range	0.40.63 A	
[Ui] rated insulation voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1	

## Complementary

Network Frequency	0400 Hz
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 Ir IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A signalling circuit
Permissible current	3 A 120 V AC-15 signalling circuit 0.22 A 125 V DC-13 signalling circuit
[Ue] rated operational voltage	690 V AC 0400 Hz power circuit IEC 60947-4-1
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
[Uimp] rated impulse withstand voltage	6 kV
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Control type	Red push-button stop Blue push-button reset

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Temperature compensation -4140 °F (-2060 °C)		
Connections - terminals	Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) flexible without cable end	
	Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible with cable end	
	Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) solid without cable end	
	Power circuit screw clamp terminals 1 0.0020.02 in² (1.510 mm²) flexible without cable end	
	Power circuit screw clamp terminals 1 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> ) flexible with cable end	
	Power circuit screw clamp terminals 1 0.0020.009 in² (16 mm²) solid without cable end	
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals	
Height	2.6 in (66 mm)	
Width	1.8 in (45 mm)	
Depth	2.8 in (70 mm)	
Net Weight	0.273 lb(US) (0.124 kg)	

## **Environment**

Climatic withstand	IACS E10	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1	
Ambient Air Temperature for Storage	-76158 °F (-6070 °C)	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7	
Dielectric strength	1.89 kV 50 Hz IEC 60947-1	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495	
Product Certifications	IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA	

# Ordering and shipping details

Category	US10I1222347
Discount Schedule	0112
GTIN	3389110346749
Returnability	Yes
Country of origin	FR

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.93 in (4.9 cm)
Package 1 Width	3.03 in (7.7 cm)
Package 1 Length	3.46 in (8.8 cm)
Package 1 Weight	4.8 oz (137 g)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	7.98 lb(US) (3.62 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	384
Package 3 Height	29.53 in (75 cm)
Package 3 Width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)
Package 3 Weight	154.156 lb(US) (69.924 kg)

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	13
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	224fb0ea-2bc1-482e-b6b4-c1bdd9779659
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No