

# TeSys Deca thermal overload relays , 17...25A , class 10A

LRD3322

Product availability: Stock - Normally stocked in distribution facility

### Main

Range	TeSys	
product name	TeSys LRD TeSys Deca	
Product or Component Type	Differential thermal overload relay	
Device short name	LRD	
Relay application	Motor protection	
Product Compatibility	LC1D80 LC1D95	
network type	DC AC	
Thermal overload class	Class 10A IEC 60947-4-1	
Thermal protection adjustment range	1725 A	
[Ui] rated insulation voltage	Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL	

### Complementary

Network Frequency	0400 Hz	
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor	
Tripping threshold	1.14 +/- 0.06 Ir IEC 60947-4-1	
Auxiliary contact composition	1 NO + 1 NC	
[Ith] conventional free air thermal current	5 A signalling circuit	
Permissible current	0.72 A 500 V AC-15 signalling circuit 0.06 A 440 V DC-13 signalling circuit	
[Ue] rated operational voltage	1000 V AC 0400 Hz power circuit IEC 60947-4-1	
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit	
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1	
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0	
Control type	Red push-button stop Blue push-button reset	
Temperature compensation	-4140 °F (-2060 °C)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Connections - terminals	Power circuit screw clamp terminals 1 0.0060.05 in² (435 mm²) flexible without cable end Power circuit screw clamp terminals 1 0.0060.05 in² (435 mm²) flexible with cable end Power circuit screw clamp terminals 1 0.0060.05 in² (435 mm²) solid without	
	cable end Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) flexible without cable end Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) flexible with	
	cable end Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) solid without cable end	
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.7 lbf.in (9 N.m) screw clamp terminals	
Height	3.2 in (81 mm)	
Width	2.8 in (70 mm)	
Depth	4.5 in (115 mm)	
Net Weight	1.12 lb(US) (0.51 kg)	

### **Environment**

Climatic withstand	IACS E10		
IP degree of protection	IP20 conforming to IEC 60529		
Ambient air temperature for operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1		
Ambient Air Temperature for Storage	-76158 °F (-6070 °C)		
Flame retardance	V1 conforming to UL 94		
Mechanical robustness	Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7		
Dielectric strength	2.2 kV 50 Hz IEC 60947-1		
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495		
Product Certifications	IEC UL CSA CCC EAC ATEX INERIS UKCA		

# Ordering and shipping details

Category	US10I1222347	
Discount Schedule	0112	
GTIN	3389110519822	
Returnability	Yes	
Country of origin	FR	

# **Packing Units**

Unit Type of Package 1	PCE		

Number of Units in Package 1	1	
Package 1 Height	3.15 in (8.000 cm)	
Package 1 Width	4.72 in (12.000 cm)	
Package 1 Length	3.35 in (8.500 cm)	
Package 1 Weight	17.566 oz (498.000 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	12	
Package 2 Height	5.91 in (15.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	13.900 lb(US) (6.305 kg)	

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	6
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No