Specifications



TeSys Deca, thermal overload relay, 30 to 40 A, class 10A, for LC1D80 and LC1D95

LRD3355

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
product name	TeSys LRD TeSys Deca
Product or Component Type	Differential thermal overload relay
Device short name	LRD
Relay application	Motor protection
Product Compatibility	LC1D80 LC1D95
network type	DC AC
Thermal overload class	Class 10A IEC 60947-4-1
Thermal protection adjustment range	3040 A
[Ui] rated insulation voltage	Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL

Complementary

Network Frequency	0400 Hz	
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor	
Tripping threshold	1.14 +/- 0.06 lr IEC 60947-4-1	
Auxiliary contact composition	1 NO + 1 NC	
[Ith] conventional free air thermal current	5 A signalling circuit	
Permissible current	0.72 A 500 V AC-15 signalling circuit 0.06 A 440 V DC-13 signalling circuit	
[Ue] rated operational voltage	1000 V AC 0400 Hz power circuit IEC 60947-4-1	
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit	
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1	
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0	
Control type	Red push-button stop Blue push-button reset	
Temperature compensation	-4140 °F (-2060 °C)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Connections - terminals	Power circuit screw clamp terminals 1 0.0060.05 in ² (435 mm ²) flexible without cable end
	Power circuit screw clamp terminals 1 0.0060.05 in ² (435 mm ²) flexible with cable end
	Power circuit screw clamp terminals 1 0.0060.05 in ² (435 mm ²) solid without cable end
	Control circuit screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²) flexible without cable end
	Control circuit screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²) flexible with cable end
	Control circuit screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²) solid without cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.7 lbf.in (9 N.m) screw clamp terminals
Height	3.2 in (81 mm)
Width	2.8 in (70 mm)
Depth	4.5 in (115 mm)
Net Weight	1.12 lb(US) (0.51 kg)

Environment

Climatic withstand	IACS E10	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1	
Ambient Air Temperature for Storage	-76158 °F (-6070 °C)	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7	
Dielectric strength	2.2 kV 50 Hz IEC 60947-1	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495	
Product Certifications	IEC UL CSA CCC EAC ATEX INERIS UKCA	

Ordering and shipping details

Category	US10I1222347
Discount Schedule	0112
GTIN	3389110519938
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1

PCE

Number of Units in Package 1	1
Package 1 Height	3.07 in (7.800 cm)
Package 1 Width	4.72 in (12.000 cm)
Package 1 Length	3.39 in (8.600 cm)
Package 1 Weight	17.566 oz (498.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	13.922 lb(US) (6.315 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	192
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	245.586 lb(US) (111.396 kg)

Contractual warranty

Warranty

18 months

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	6
Environmental Disclosure	Product Environmental Profile

Use Better

Yes
Yes
China RoHS declaration
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No