

TeSys LRF - electronic thermal overload relay - 60...100 A - class 10

LR9F5367

Discontinued on: Jun 15, 2023

① Discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
product name	TeSys LRF
Device short name	LR9F
Product or Component Type	Electronic thermal overload relay
Relay application	Motor protection
Product Compatibility	LC1F115LC1F185
network type	AC
Thermal overload class	Class 10 IEC 60947-4
Thermal protection adjustment range	60100 A

Complementary

Network Frequency	50/60 Hz	
Mounting support	Direct on contactor Plate	
Tripping threshold	1.12 +/- 0.06 In tripping IEC 60947-4-1	
Surge withstand	4 kV IEC 61000-4-5	
Contacts type and composition	1 NO + 1 NC	
[Ith] conventional free air thermal current	5 A control circuit	
[Ue] rated operational voltage	1000 V AC 50/60 Hz power circuit VDE 0110 group C	
[Ui] rated insulation voltage	Power circuit 1000 V AC IEC 60947-4	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-1	
Phase failure sensitivity	Tripping in 4 s +/- 20 % IEC 60947-4-1	
Reset	Manual reset on front relay	
Control type	Dial White full-load current adjustment Test button Red Push-button Red reset Push-button stop	
Local signalling	Trip indicator	
Temperature compensation	-4158 °F (-2070 °C)	
Current consumption	<= 5 mA no-load	
switching capacity for alarm	0150 mA	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<2.5 V closed state	
Control circuit screw clamp terminals 1 0.0010.004 in² (0.752.5 mm²) flexible - with cable end	
Control circuit screw clamp terminals 1 0.0010.004 in ² (0.752.5 mm ²) solid	
Control circuit screw clamp terminals 1 0.0010.006 in² (0.754 mm²) flexible - without cable end	
Control circuit screw clamp terminals 2 0.0020.002 in² (11.5 mm²) flexible - with cable end	
Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²) flexible -	
without cable end	
Control circuit screw clamp terminals 2 0.002 in ² (1 mm ²) solid	
Power circuit lugs-ring terminals M8	
Control circuit 1.2 N.m screw clamp terminals	
Power circuit 18 N.m screw clamp terminals	
3.8 in (96 mm)	
4.5 in (115 mm)	
4.9 in (123.5 mm)	
2.0 lb(US) (0.9 kg)	

Environment

61000-4-2
0 V/m IEC 61000-4-3

Ordering and shipping details

Category	US10l1222334	
Discount Schedule	0112	
GTIN	3389110565997	
Returnability	Yes	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE		
------------------------	-----	--	--

Number of Units in Package 1	1	
Package 1 Height	5.12 in (13.000 cm)	
Package 1 Width	6.30 in (16.000 cm)	
Package 1 Length	5.91 in (15.000 cm)	
Package 1 Weight	31.005 oz (879.000 g)	
Unit Type of Package 2	S04	
Number of Units in Package 2	12	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	15.75 in (40.000 cm)	
Package 2 Length	23.62 in (60.000 cm)	
Package 2 Weight	25.113 lb(US) (11.391 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	48	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	23.62 in (60.000 cm)	
Package 3 Length	31.50 in (80.000 cm)	
Package 3 Weight	122.586 lb(US) (55.604 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	133
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	D5a17874-1166-4927-b008-33d15e304a41
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No