



# Product data sheet

Specifications



## Modbus TCP communication card, 10 to 100Mbps, 1 x RJ45 connector

VW3A3310D

-  **Discontinued on:** Jan 23, 2021
-  **To be end-of-service on:** Jan 24, 2026

 **Discontinued - Service only**

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Main

Product or Component Type	Communication card
Range Compatibility	Altivar 61 Altivar 71 Altivar 71Q Altivar 61Q
Communication Port Protocol	Modbus TCP
Product Specific Application	For daisy chain mounting
Connector Type	1 RJ45
Transmission Rate	100 Mbps 10 Mbps
Physical interface	Ethernet 2
Web services	Altivar viewer Ethernet statistics Altivar chart IO Scanner FDR Agent Data editor E-mail Security

### Complementary

Exchange mode	Half duplex and full duplex
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3
Communication network type	IP RFC791
Communication transport type	UDP 8 connections maximum TCP RFC793
Concept	Transparent Ready class C20
Web server	Embedded

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Communication service	CiA 402 profile I/O profile Communication monitoring can be inhibited, adjustable Diagnostics (08) FTP I/O scanning service can be inhibited Read device identification (43) Read holding registers (03) Read input registers (04) Read/write multiple registers (23) SNMP TFTP Write multiple registers (16) Write single register (06)
Display type	1 LED 10/100 Mbps (speed) 1 LED FLT (Ethernet fault) 1 LED RX (reception) 1 LED STS (IP address) 1 LED TX (transmission) Graphic display terminal control word received Graphic display terminal reference received Web server
Net Weight	0.7 lb(US) (0.3 kg)

## Ordering and shipping details

Category	US1CP4C22135
Discount Schedule	CP4C
GTIN	3389119218504
Returnability	No
Country of origin	ID

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7.000 cm)
Package 1 Width	6.77 in (17.200 cm)
Package 1 Length	9.25 in (23.500 cm)
Package 1 Weight	9.947 oz (282.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.490 lb(US) (2.490 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	49
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Use Better

Materials and Substances	
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	019506db-afc0-4f0c-aa81-986eb742c8db
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a>
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations