

universal power supply, Phaseo, 1 or 2 phase, 100 to 500 V, 24 V, 10 A

ABL8RPS24100

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon Power Supply	
Product or Component Type	Power supply	
Power supply type	Regulated switch mode	
Nominal input voltage	100120 V AC single phase N-L1 200500 V AC phase to phase L1-L2	
Kw Rating	240 W	
Output voltage	24 V DC	
Power supply output current	10 A	
Permissible temporary current boost	1.5 x In for 4 s)	
Anti-harmonic filter	Low frequency harmonic currents	

Complementary

oompromontary		
Efficiency at full load	170550 V AC 85132 V AC	
Inrush current	30 A	
Power factor	0.68 at 240 V AC 0.69 at 120 V AC	
Efficiency	87 %	
Output voltage adjustment	2428.8 V adjustable	
Power dissipation in W	31 W	
Provided equipment	Power factor correction filter IEC 61000-3-2	
Output protection type	Against overload, protection technology: manual or automatic reset Against overvoltage, protection technology: 3032 V, manual reset Against short-circuits, protection technology: manual or automatic reset Against undervoltage, protection technology: tripping if U < 21.6 V Thermal, protection technology: automatic reset	
Connections - terminals	Removable screw terminal block 2 x 2.5 mm², diagnostic relay Screw type terminals 3 x 0.53 x 4 mm², AWG 22AWG 12) input connection Screw type terminals 1 x 0.51 x 4 mm², AWG 22AWG 12) input ground connection Screw type terminals 4 x 0.54 x 4 mm², AWG 22AWG 12) output connection Screw type terminals 1 x 0.51 x 4 mm², AWG 22AWG 12) output ground connection	
Status LED	LED (green and red) output voltage LED (green, red and orange) output current	
Depth	5.7 in (145 mm)	
Height	4.9 in (125 mm)	
Width	3.4 in (86 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	2.2 lb(US) (1 kg)	
Output coupling	Parallel Series	
Marking	CE	
Mounting support	35 x 7.5 mm symmetrical DIN rail 35 x 15 mm symmetrical DIN rail	
Operating position	Vertical	
Supply	SELV IEC 60950-1 SELV IEC 60204-1 SELV IEC 60364-4-41	
Dielectric strength	3500 V with between input and ground 4000 V with between input and output 500 V with between output and ground	

Environment

Standards	UL 508 CSA C22.2 No 60950-1	
	EN/IEC 62368-1	
Product certifications	CCSAus	
	EAC	
	KC	
	RCM	
	UL	
Environmental characteristic	EMC conforming to IEC 61000-6-1	
	EMC conforming to IEC 61000-6-3	
	EMC conforming to EN 55024	
	EMC conforming to IEC 61000-6-4	
	EMC conforming to EN/IEC 61204-3	
	Safety conforming to IEC 60950-1	
	Safety conforming to EN/IEC 61204-3	
Operating altitude	6561.68 ft (2000 m)	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	122140 °F (5060 °C) with derating factor mounting position A < 6561.68 ft (2000 m)	
	-13122 °F (-2550 °C) without derating mounting position A < 6561.68 ft (2000 m)	

Ordering and shipping details

Category	US1CP1222525
Discount Schedule	CP12
GTIN	3389119405621
Returnability	Yes
Country of origin	РН

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.33 in (11.000 cm)
Package 1 Width	6.57 in (16.700 cm)
Package 1 Length	7.17 in (18.200 cm)
Package 1 Weight	3.627 lb(US) (1.645 kg)
Unit Type of Package 2	P06

Number of Units in Package 2	60
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	247.844 lb(US) (112.420 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	566
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	974297e5-68e4-4a61-9a40-1443e8973a62
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again


○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

ABL8RPS24100

Dimensions Drawings

Regulated Switch Mode Power Supplies

Dimensions



ABL 8	a in mm	a in in.	b in mm	b in in.
RPS24030	125	4.92	45	1.77
RPS24050	125	4.92	56	2.20
RPS24100	145	5.71	86	3.39
RPM24200	145	5.71	146	5.75
WPS24200	160	6.30	96	3.78
WPS24400	160	6.30	166	6.54


Product data sheet

ABL8RPS24100

Connections and Schema

Regulated Switch Mode Power Supply

Internal Wiring Diagram




ABL8RPS24100


Regulated Switch Mode Power Supply

Line Supply Wiring Diagram


Single-phase (L-N) 100 to 120 V



Phase-to-phase (L1-L2) 200 to 500 V




Single-phase (L-N) 200 to 500 V




Regulated Switch Mode Power Supplies

Series or Parallel Connection

Series Connection



(1) Two Shottky diodes Imin = power supply In and Vmin = 50 V Parallel Connection



Family	Series	Parallel
ABL 8RPS/8RPM/8WPS	2 products max. (1)	2 products max.

NOTE: Series or parallel connection is only recommended for products with identical references.

For better availability, the power supplies can also be connected in parallel using the **ABL8RED24400** Redundancy module.

ABL8RPS24100


Performance Curves

Regulated Switch Mode Power Supplies

Derating

The ambient temperature is a determining factor that limits the power an electronic power supply can deliver continuously. If the temperature around the electronic components is too high, their life will be significantly reduced. The nominal ambient temperature for the Universal range of Phaseo power supplies is 50°C. Above this temperature, derating is necessary up to a maximum temperature of 60°C.

The graph below shows the power (in relation to the nominal power) that the power supply can deliver continuously, depending on the ambient temperature.




X Maximum operating temperature (°C)
ABL 8RPM, ABL 8RPS, ABL 8WPS mounted vertically
Derating should be considered in extreme operating conditions:

- Intensive operation (output current permanently close to the nominal current, combined with a high ambient temperature)
- Output voltage set above 24 Vdc (to compensate for line voltage drops, for example)
- Parallel connection to increase the total power

Regulated Switch Mode Power Supply


Load Limit

Manual Reset Protection Mode




(1) Boost 4s

Automatic Reset Protection Mode



(1) Boost 4s "Boost" Repeat Accuracy



This type of operation is described in detail in the user manual, which can be downloaded from the website.

Image of product / Alternate images

Alternative

